## WHAT IS CLAIMED:

2

1	1 1. A golf target apparatus comprising:	
2	2 a portable base unit having at le	east a pair of wheels;
3	a vertical support member have	ring a bottom end mounted to the portable
4	4 base unit such that the vertical support	member projects upward from the portable
5	5 base unit and wherein the vertical	support member has a top end having a
6	6 mounting assembly; and	
7	7 a target assembly having a target	get support structure, a target surface and a
8	8 tilt assembly, wherein the tilt assembly	y operably connects the mounting assembly
9	9 and the target support structure such	that a target profile has an adjustable tilt
10	range from 0 degrees to 90 degrees.	
1	1 2. The golf target apparatus of claim 1, where	n the portable base unit comprises a self-
2	contained motor for propelling movement of the golf target apparatus.	
1	1 3. The golf target apparatus of claim 1, wherein	the portable base unit further comprises a

- 1 4. The golf target apparatus of claim 1, wherein the portable base unit has a frame adapted
- 2 for receiving weighting means to fix the position of the golf target apparatus.

towing member for towing the golf target apparatus.

- 1 5. The golf target apparatus of claim 1, wherein the portable base unit comprises a plurality
- 2 of extensions attached to the portable base unit.
- 1 6. The golf target apparatus of claim 1, further comprising a display apparatus, the display
- 2 apparatus being rotatably couplable to the target structure such that the display apparatus is
- 3 viewable throughout the tilt range of the target structure.
- 1 7. The golf target apparatus of claim 6, wherein the display apparatus comprises an
- 2 electronic display.

1

- 1 8. The golf target apparatus of claim 7, wherein the electronic display displays an electronic
- 2 message selected from the group consisting essentially of: a target yardage, a stock ticker, an
- 3 advertisement, a listing of sports results, a tee box status, and a video broadcast.
- 1 9. The golf target apparatus of claim 1, wherein the vertical support comprises a first
- 2 support member and a second support member, wherein the first support member is attached to
- 3 the mounting assembly and the second support member is attached to the portable base unit, and
- 4 wherein the first support member is slidably adjustable with respect to the second support
- 5 member for adjusting an overall height of the target assembly.
- 1 10. The golf target apparatus of claim 1, wherein the target support structure has an internal,
- 2 concave shape defined by a plurality of support ribs, a plurality of cross-members and a

- 3 perimeter wall and wherein the target surface is fixedly attached to target support structure at the
- 4 perimeter wall.
- 1 11. The golf target apparatus of claim 10, wherein an internal portion of the target surface is
- 2 adjustably attached to the target support structure such that the target surface and the target
- 3 support structure cooperatively retain a golf ball that hits the target surface.
- 1 12. A method for practicing golf using at least one portable target comprising:
- selecting a tee area such that at least one golfer has space for hitting a golf ball;
- positioning the at least one portable target such that the target resides within view
- 4 of the tee area; and
- 5 presenting a target surface on the portable target to the golfer such that the golfer
- has an aiming point when hitting the golf ball, the target surface including a tilt
- 7 adjustment means for selectively varying a profile of the target surface with respect to the
- 8 tee area.
- 1 13. The method of claim 12, wherein a plurality of portable targets are positioned such that
- 2 the plurality of targets are within view of the tee area.
- 1 14. The method of claim 13, wherein each of the plurality of portable targets are selectively
- 2 adjustable using the adjustment means to present a plurality of differing target profiles.

- 1 15. The method of claim 12, wherein positioning the at least one portable target comprises
- 2 towing the at least one portable target to a desired location.
- 1 16. The method of claim 12, wherein positioning the at least one portable target comprises
- 2 propelling the at least one portable target to a desired location using a self-contained drive means
- 3 on the at least portable target.
- 1 17. The method of claim 12, further comprising displaying visual information to the at least
- 2 one golfer with a display means attached to the at least one portable target.
- 1 18. The method of claim 17, wherein the display means is a printed media or an electronic
- 2 display
- 1 19. The method of claim 18, wherein the visual information communicated to the at least one
- 2 golfer is selected from the group consisting essentially of: an advertisement, a target distance, a
- 3 stock ticker, a listing of sports results, a tee box status, and a video broadcast.